

CO2 STORAGE SAFETY STROBES CM-1026-5,6

The strobes provide a bright, flashing indicator and alarm for any of our CO2 or Oxygen Storage Safety Alarms. Both of the CM-1026 strobes clearly indicate the alarm level to anyone in the room.

FEATURES

• Controlled by the relay outputs on the RAD sensor unit

WORKS WITH

- RAD-0102-6 Remote CO2 Storage Safety 3 Alarm
- RAD-0200-2 Remote CO2 + Oxygen Storage Safety 3 Alarm
- RAD-0002 Remote Oxygen Depletion Safety Alarm
- RAD-0012 Remote Oxygen Enrichment Safety Alarm

SPECIFICATIONS

- Height:
 - CM-1026-5: 16 inches - CM-1026-6: 11.5 inches
- Diameter: 1.5 inches
- · Alarm Relays:
 - Green Normal air
 - Clear Alarm level 1/Relay 1 triggered
 - Amber Alarm level 2/Relay 2 triggered
 - Red Alarm level 3/Relay 3 triggered.
- Mounting Bracket Included

ELECTRICAL

Safety Strobe Tower

- Six foot cable and connector included
- CM-1026-5: 100-240 VAC to 24 VDC power supply included
- CM-1026-6: User supplied 24 VDC power required
- Wiring diagram available

INDUSTRIES

Restaurants



Beverage

INSTALL PHOTOS



